


LAMP PHOTOMETRIC REPORT

MODEL: 93ZFLD6040/BL		
POWER: 60W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 5757.1 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	5263	6194	6627	5622	5336	5816	6711	6429	0- 10	597.3	597.3	10.4
20	3723	4905	5945	4405	3730	4573	6179	5211	10- 20	1523	2121	36.8
30	2333	3543	3910	2978	1991	3251	4239	3860	20- 30	1885	4006	69.6
40	246.0	1562	1346	754.2	215.8	957.6	1542	1969	30- 40	1275	5280	91.7
50	61.26	178.0	268.5	85.81	53.51	102.7	288.7	266.8	40- 50	382.5	5663	98.4
60	20.48	30.52	52.99	18.86	17.34	21.50	55.38	36.31	50- 60	75.52	5738	99.7
70	4.721	6.421	6.908	2.959	2.414	3.667	8.027	7.594	60- 70	16.75	5755	100
80	0.2801	0.4225	0.4686	0.3117	0.2879	0.3183	0.3838	0.3388	70- 80	1.692	5757	100
90	0.1964	0.2330	0.3536	0.2790	0.2933	0.3630	0.4221	0.3200	80- 90	0.3362	5757	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:30 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```