


LAMP PHOTOMETRIC REPORT

MODEL: 955LED101T/BL		
POWER: 9W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 831.82 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	317.6	316.9	316.8	317.4	316.9	317.9	318.1	317.5	0- 10	30.65	30.65	3.68
20	296.0	294.6	294.2	295.6	294.9	296.7	297.1	295.7	10- 20	86.88	117.5	14.1
30	261.1	259.4	258.9	260.8	260.0	262.6	263.0	261.1	20- 30	128.8	246.3	29.6
40	215.2	214.5	214.3	216.6	215.6	218.8	219.3	216.7	30- 40	149.8	396.1	47.6
50	159.3	164.5	165.6	167.8	166.6	170.2	170.9	167.0	40- 50	147.9	544.0	65.4
60	106.0	113.2	117.3	119.2	117.4	121.7	122.6	115.4	50- 60	126.6	670.6	80.6
70	62.09	67.63	71.95	73.56	71.23	76.14	77.41	69.47	60- 70	92.66	763.3	91.8
80	7.762	29.34	31.75	31.07	29.04	33.61	36.32	30.98	70- 80	52.99	816.3	98.1
90	0.5141	1.779	3.579	1.328	0.6093	1.360	5.267	1.311	80- 90	15.56	831.8	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:
 Test Date:01 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```